

STERLING

BLOWER FAN

(Model F-29A)

The F-29A fan is designed for floor drying, water damage restoration, and ventilation. This high velocity 2900 CFM fan operates at 2.9 amps and has a built-in GFCI outlet for daisy chaining multiple units. Constructed using a tough rotomolded housing, the F-29A is built to resist impacts, constant handling and transportation to and from jobsites.

FEATURES:

- Maximum 2900 CFM for fast, efficient drying.
- Powerful, yet efficient motor operating at 2.9 amps.
- Built-in GFCI circuit allows you to “daisy chain” multiple units together to service large areas where power outlets are limited or not available.
- Three-position switch for selecting the appropriate operating speed and air flow for the job.
- Large molded-in cord wrap for quick, easy storage of power cord.
- Off-set carrying handle distributes motor weight evenly for comfortable grip and transport.
- Protected with a one-year warranty on the motor, five-years on the polyethylene housing.
- ETL approved.

TECHNICAL SPECIFICATIONS:

Item Number:	150-1602-10
Power:	115V, 60Hz
Motor:	1/3 Horsepower
Amps:	2.9 amps maximum
Fan Speed:	890/980/1080 RPM
CFM:	2900 maximum
Power cord:	24 feet
Weight:	27 lbs.
Dimensions:	17" x 19" x 19"



For More Information Visit SterlingNA.com
Or Call [844-822-7787](tel:844-822-7787) (844-Vacs R Us)

